

BL - 10				zurückgelegte Wegstrecke in mm / Motorumdrehung																									
		3,14		25,0	25,1	25,2	25,3	25,4	25,5	25,6	25,7	25,8	25,9	26,0	26,1	26,2	26,3	26,4	26,5	26,6	26,7	26,8	26,9	27,0	27,1	27,2	27,3	27,4	
Durchm. in mm				78,54	78,85	79,17	79,48	79,80	80,11	80,42	80,74	81,05	81,37	81,68	82,00	82,31	82,62	82,94	83,25	83,57	83,88	84,19	84,51	84,82	85,14	85,45	85,77	86,08	
Umfang in mm				19,25 mm bis 20,25mm																									
Motor	Achse	Übers.																											
10		<i>DM</i>																											
	39		3,90	20,14	20,22	20,30	20,38	20,46	20,54	20,62	20,70	20,78	20,86	20,94	21,02	21,11	21,19	21,27	21,35	21,43	21,51	21,59	21,67	21,75	21,83	21,91	21,99	22,07	
	40	20,9	4,00	19,64	19,71	19,79	19,87	19,95	20,03	20,11	20,18	20,26	20,34	20,42	20,50	20,58	20,66	20,73	20,81	20,89	20,97	21,05	21,13	21,21	21,28	21,36	21,44	21,52	
	41	21,4	4,10	19,16	19,23	19,31	19,39	19,46	19,54	19,62	19,69	19,77	19,85	19,92	20,00	20,08	20,15	20,23	20,31	20,38	20,46	20,54	20,61	20,69	20,77	20,84	20,92	21,00	
	42	21,9	4,20	18,70	18,77	18,85	18,92	19,00	19,07	19,15	19,22	19,30	19,37	19,45	19,52	19,60	19,67	19,75	19,82	19,90	19,97	20,05	20,12	20,20	20,27	20,35	20,42	20,50	
	43	22,4	4,30	18,27	18,34	18,41	18,48	18,56	18,63	18,70	18,78	18,85	18,92	19,00	19,07	19,14	19,21	19,29	19,36	19,43	19,51	19,58	19,65	19,73	19,80	19,87	19,95	20,02	